


Grade 80 Eye Sling Hook With Safety Catch

Grade 80 Alloy Steel



Product Overview

Our Grade 80 Eye Sling Hooks are a vital component for a wide range of lifting applications. Forged from high-tensile **Grade 80 alloy steel**, they offer an excellent combination of strength and durability. Each hook is fitted with a robust, **spring-loaded steel safety catch** that securely closes the hook opening, preventing the accidental release of slings, chains, or attachments. The eye connection allows for easy integration into lifting assemblies. All hooks are proof load tested, certified, and finished in a **high-visibility yellow paint**.



Technical Specifications

The following table outlines the key dimensions, Working Load Limits (W.L.L.), weights, and part codes for our range of Grade 80 Eye Sling Hooks.

LENGTH (L)	MATERIAL DIA. (H)	EYE DIA. (A)	CATCH DISTANCE (E)	W.L.L.	WEIGHT	PART CODE
133mm	27mm	25mm	22mm	2.00t	0.55Kg	G80ESHSC08
167mm	33mm	34mm	28mm	3.15t	1.05Kg	G80ESHSC10
207mm	40mm	42mm	35mm	5.30t	1.75Kg	G80ESHSC13
253mm	48mm	52mm	43mm	8.00t	3.20Kg	G80ESHSC16

Important Safety Notice: This product is intended for lifting applications and must be used in accordance with LOLER (Lifting Operations and Lifting Equipment Regulations) and other relevant safety standards. The information provided, including Working Load Limits (W.L.L.), is for guidance and reference purposes only. Dimensions and specifications are approximate and subject to manufacturing tolerances. Click **A competent person must determine the suitability of this product** for any given application. All hooks and lifting assemblies should be thoroughly inspected before each use. Deacon Products assumes no liability for the misuse, misapplication, or improper assembly of this information or our products.

