

# Self Colour Bow Nut

Conforms to B.S 3974 - Certified for Lifting



## Product Overview

Our Self-Colour Bow Nuts are a versatile lifting component designed to be threaded onto a stud or bolt to create a secure lifting point. The bow shape provides ample room for attaching hooks and slings. These bow nuts are load-rated for lifting and are supplied in a self-colour (unfinished) state, which is ideal for customers who need to weld the nut in place or apply their own specific paint or protective finish.

**Important Safety Notice: The Safe Working Load (SWL) stated is for vertical, in-line lifts only. The SWL must be reduced for any non-axial (angled) lifts.**



## Technical Specifications

The following table outlines the key dimensions and Safe Working Load (SWL) for our range of self-colour bow nuts.

Thread Dia. (D)	Eye Diameter (E)	S.W.L. (Vertical Lift)
M10	25mm	0.36t
M12	30mm	0.53t
M16	30mm	1.01t
M20	40mm	1.58t

**Important Safety Notice:** The information provided is for guidance and reference purposes only. The Safe Working Load (SWL) stated is for **vertical, in-line lifts only** and conforms to B.S 3974. The SWL must be reduced for any non-axial (angled) lifts. The mating male threaded component must be of a suitable grade and specification to handle the

intended load. All lifting equipment must be thoroughly inspected before each use by a competent person. Deacon Products assumes no liability for the misuse or misapplication of this information or our products.

---